

Gorham Fire and EMS <u>Town of Gorham New Hampshire</u>

347 Main Street Gorham NH 03581 603-466-2549



Wood Burning Stove Inspection Form

| Owners Name: | | | | Date: | | |
|----------------------|-----|----|--------------------------------|-------|----|--|
| Owners Address: | | | | | | |
| Location in home: | | | | | | |
| Main Source of Heat: | Yes | No | Supplemental Heat Source only: | Yes | No | |

| Installed by: | Homeowner | Contractor | Other(specify) | | |
|------------------|-----------|------------|----------------|---------------|--|
| Contractor Name | e: | | | Install Date: | |
| Reason for inspe | ction: | | | | |

Safety Inspection

| | Safety Inspection Item | Pass | Fail | N/A | Comments |
|----|--|------|------|-----|----------|
| | Stove Pipe | | | | |
| 1. | Stove pipe connections tight and overlapped. | | | | |
| 2. | Damper is provided in stovepipe. | | | | |
| 3. | Stove pipe has 2 or less 90-degree bends. | | | | |
| 4. | Horizontal stove pipe sections raise at ¼" per linear foot. | | | | |
| 5. | Stove pipe horizontal sections have 18" clearance to ceiling. | | | | |
| | Masonry Chimney | | | | |
| 6. | Bricks in good condition with mortar. | | | | |
| 7. | Liner is in good condition with minimal creosote buildup. | | | | |
| 8. | Single unit connected to flu. | | | | |
| | Prefabricated (Factory Built) | | | | |
| 9. | Chimney is UL listed and installed according to manufacturer recommendations. | | | | |
| | If passing through combustible material, a properly installed thimble is present. Single unit connected to flu. | | | | |
| | | | | | |




Gorham Fire and EMS <u>Town of</u> Gorham New Hampshire

347 Main Street Gorham NH 03581 603-466-2549



Safety Inspection Continued

| Safety Inspection Item | Pass | Fail | N/A | Comments |
|-------------------------------------|------|------|-----|----------|
| Clearances | | | | |
| 12. Noncombustible material minimum | | | | |
| 18" from side with opening door. | | | | |
| 13. Noncombustible material minimum | | | | |
| 12" from sides of unit. | | | | |
| 14. Minimum 18" from wall when | | | | |
| noncombustible and air gapped. | | | | |
| 15. Minimum 36" from wall if | | | | |
| combustible. | | | | |
| 16. Stove pipe minimum 18" from | | | | |
| unprotected wall. | | | | |





Gorham Fire and EMS Town of Gorham New Hampshire

347 Main Street Gorham NH 03581 603-466-2549



This wood stove meets Fire Department requirements for safe operation on _____

| Signed: | | | | |
|---|---|------|--|--|
| Fire Inspector | Fire Inspector | Date | | |
| This wood stove does not meet the Fire Departme | ent requirements for safe operation on | | | |
| Signed: | Printed name: | | | |
| Fire Inspector | Fire Inspector | Date | | |
| The following items must be corrected: | | | | |
| | | | | |
| | | | | |
| operation. | and now meets the requirements for safe | | | |
| Signed: | Printed name: | | | |
| Fire Inspector | Fire Inspector | Date | | |